

# FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO

Sekisui Specialty Chemicals America, LLC

AUTHORIZING THE OPERATION OF

Pasadena Plant  
Industrial Organic Chemicals

LOCATED AT

Harris County, Texas

Latitude 29° 43' 2" Longitude 95° 11' 27"

Regulated Entity Number: RN103012183

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: O2308 Issuance Date: November 13, 2014

---

For the Commission

## Table of Contents

Section	Page
General Terms and Conditions .....	1
Special Terms and Conditions .....	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting .....	1
Additional Monitoring Requirements .....	11
New Source Review Authorization Requirements .....	12
Compliance Requirements.....	13
Risk Management Plan .....	15
Protection of Stratospheric Ozone.....	15
Temporary Fuel Shortages (30 TAC § 112.15) .....	15
Permit Location.....	15
Permit Shield (30 TAC § 122.148) .....	16
Attachments .....	17
Applicable Requirements Summary .....	18
Additional Monitoring Requirements .....	75
Permit Shield.....	88
New Source Review Authorization References.....	94
Appendix A .....	100
Acronym List .....	101

## **General Terms and Conditions**

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

## **Special Terms and Conditions: Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting**

1. Permit holder shall comply with the following requirements:
  - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
  - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.

- C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
  - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
  - E. Emission units subject to 40 CFR Part 63, Subparts A, F, G, H, and FFFF as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, §§ 113.100, 113.110, 113.120, 113.130, and 113.890 respectively which incorporates the 40 CFR Part 63 Subpart by reference.
2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
- A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
  - B. Title 30 TAC § 101.3 (relating to Circumvention)
  - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
  - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
  - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
  - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
  - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
  - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
  - I. Title 30 TAC § 101.222 (relating to Demonstrations)
  - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)

3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:

A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1, shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:

- (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(1)(E)
- (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
- (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO<sub>x</sub>, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the “Applicable Requirements Summary” attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:
  - (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
  - (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum

required value does not constitute creation of an alternative fuel.

- (3) Records of all observations shall be maintained.
- (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
- (5) Compliance Certification:
  - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
  - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement.

However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.
- B. Certification of opacity readers determining opacities under Method 9 (as outlined in 40 CFR Part 60, Appendix A) to comply with opacity monitoring requirements shall be accomplished by completing the Visible Emissions Evaluators Course, or approved agency equivalent, no more than 180 days before the opacity reading.
- C. For emission units with contributions from uncombined water, the permit holder shall comply with the requirements of 30 TAC § 111.111(b).
- D. Permit holders for sites that have materials handling, construction, roads, streets, alleys, and parking lots shall comply with the following requirements:
  - (i) Title 30 TAC § 111.143 (relating to Materials Handling)
  - (ii) Title 30 TAC § 111.145 (relating to Construction and Demolition)
  - (iii) Title 30 TAC § 111.147 (relating to Roads, Streets, and Alleys)
  - (iv) Title 30 TAC § 111.149 (relating to Parking Lots)
- E. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
  - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
  - (ii) Sources with an effective stack height ( $h_e$ ) less than the standard effective stack height ( $H_e$ ), must reduce the allowable emission level by multiplying it by  $[h_e/H_e]^2$  as required in 30 TAC § 111.151(b)

- (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- F. Outdoor burning, as stated in 30 TAC § 111.201, shall not be authorized unless the following requirements are satisfied:
  - (i) Title 30 TAC § 111.205 (relating to Exception for Fire Training)
  - (ii) Title 30 TAC § 111.207 (relating to Exception for Recreation, Ceremony, Cooking, and Warmth)
  - (iii) Title 30 TAC § 111.219 (relating to General Requirements for Allowable Outdoor Burning)
  - (iv) Title 30 TAC § 111.221 (relating to Responsibility for Consequences of Outdoor Burning)
- 4. For industrial wastewater specified in 30 TAC Chapter 115, Subchapter B, the permit holder shall comply with the following requirements:
  - A. Title 30 TAC § 115.145 (relating to Approved Test Methods)
  - B. Title 30 TAC § 115.146 (relating to Recordkeeping Requirements)
  - C. Title 30 TAC § 115.147(1) (relating to Exemptions)
  - D. Title 30 TAC § 115.148 (relating to Determination of Wastewater Characteristics)
- 5. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter F, Division 3, Degassing of Storage Tanks, Transport Vessels and Marine Vessels:
  - A. For degassing of stationary VOC storage tanks, the permit holder shall comply with the following requirements:
    - (i) Title 30 TAC § 115.541(a) - (c) (relating to Emission Specifications)
    - (ii) Title 30 TAC § 115.541(f) (relating to Emission Specifications), for floating roof storage tanks
    - (iii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.
    - (iv) Title 30 TAC § 115.542(b) - (d), (relating to Control Requirements)

- (v) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)
- (vi) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections
- (vii) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring
- (viii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices
- (ix) Title 30 TAC § 115.544(b)(2)(A) - (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)
- (x) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring
- (xi) Title 30 TAC § 115.544(c), and (c)(1) - (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xii) Title 30 TAC § 115.545(1) - (7), (9) - (11) and (13) (relating to Approved Test Methods)
- (xiii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping
- (xiv) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) - (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)
- (xv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xvi) Title 30 TAC § 115.546(b) (relating to Recordkeeping and Notification Requirements), for notification
- (xvii) Title 30 TAC § 115.547(4) (relating to Exemptions)

B. For the degassing of all transport vessels with a nominal capacity of 8,000 gallons or more, the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 115.541(a) - (c) and (d) (relating to Emission Specifications)

- (ii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.
- (iii) Title 30 TAC § 115.542(b), (c) and (e) (relating to Control Requirements)
- (iv) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)
- (v) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections
- (vi) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring
- (vii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices
- (viii) Title 30 TAC § 115.544(b)(2)(A) - (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)
- (ix) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring
- (x) Title 30 TAC § 115.544(c), and (c)(1) - (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xi) Title 30 TAC § 115.545(1) - (11) and (13) (relating to Approved Test Methods)
- (xii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping
- (xiii) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) - (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)
- (xiv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xv) Title 30 TAC § 115.546(b) (relating to Recordkeeping and Notification Requirements), for notification

6. The permit holder shall comply with the following requirements of 30 TAC Chapter 117:
  - A. For boilers, process heaters, and stationary reciprocating engines exempt from Subchapter D, Division 1 at minor sources of NO<sub>x</sub> under 30 TAC § 117.2003(a), the permit holder shall comply with 30 TAC §§ 117.2030(c), 117.2035(g), 117.2045(b) and 117.2045(c).
7. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
  - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
  - B. Title 40 CFR § 60.8 (relating to Performance Tests)
  - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
  - D. Title 40 CFR § 60.12 (relating to Circumvention)
  - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
  - F. Title 40 CFR § 60.14 (relating to Modification)
  - G. Title 40 CFR § 60.15 (relating to Reconstruction)
  - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
8. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
9. For the chemical manufacturing facilities with a 40 CFR Part 63, Subpart G Group 2 wastewater stream, the permit holder shall comply with (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
  - A. Title 40 CFR § 63.132(a), (a)(1), and (a)(1)(i) (relating to Process Wastewater Provisions - General)
  - B. Title 40 CFR § 63.146(b)(1) (relating to Process Wastewater Provisions - Reporting)
  - C. Title 40 CFR § 63.147(b)(8) (relating to Process Wastewater Provisions - Recordkeeping)

10. For the transfer of gas streams having the characteristics specified in § 63.107(b) - (h) or § 63.107(i) the permit holder shall comply with the following requirements:
  - A. Title 40 CFR § 63.113(i) (relating to Process Vent Provisions - Reference Control Technology).
  - B. Title 40 CFR § 63.152(b)(6), (c)(4)(iv) and (d)(4) (relating to General Reporting and Continuous Records).
11. For the chemical manufacturing facilities subject to leak detection requirements in 40 CFR Part 63, Subpart G, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
  - A. General Leak Detection Requirements:
    - (i) Title 40 CFR § 63.148(d)(1) - (3), and (e) (relating to Leak Inspection Provisions)
    - (ii) Title 40 CFR § 63.148(c), (g), (g)(2), (h), and (h)(2) (relating to Leak Inspection Provisions), for monitoring and testing requirements
    - (iii) Title 40 CFR §§ 63.148(g)(2), (h)(2), (i)(1) - (2), (i)(4)(i) - (viii), (i)(5), and 63.152(a)(1) - (5), for recordkeeping requirements
    - (iv) Title 40 CFR §§ 63.148(j), 63.151(a)(6)(i) - (iii), (b)(1) - (2), (j)(1) - (3), 63.152(a)(1) - (5), (b), (b)(1)(i) - (ii), and (b)(4), for reporting requirements
  - B. For closed vent system or vapor collection systems constructed of hard piping:
    - (i) Title 40 CFR § 63.148(b)(1)(ii) (relating to Leak Inspection Provisions), for monitoring and testing requirements
    - (ii) Title 40 CFR § 63.148(i)(6) (relating to Leak Inspection Provisions), for recordkeeping requirements
12. For the chemical manufacturing facilities subject to transfer operations requirements in 40 CFR Part 63, Subpart G, the permit holder shall comply with the following requirements (Title 30 TAC Chapter 113, Subchapter C, § 113.120 incorporated by reference):
  - A. Title 40 CFR § 63.126(e)(1) - (2), and (f) (relating to Transfer Operations Provisions Reference Control Technology)

- B. Title 40 CFR § 63.128(f)(1) - (2) (relating to Transfer Operations Provisions - Test Methods and Procedures)
  - C. Title 40 CFR § 63.130(e) (relating to Transfer Operations Provisions - Periodic Recordkeeping and Reporting)
13. For miscellaneous chemical process facilities subject to maintenance wastewater requirements as specified in 40 CFR § 63.2485, Table 7, the permit holder shall comply with the requirements of 40 CFR § 63.105 (relating to Maintenance Wastewater Requirements) (Title 30 TAC Chapter 113, Subchapter C, § 113.890 incorporated by reference).
  14. For miscellaneous chemical process facilities with Group 2 wastewater streams subject to wastewater operations requirements in 40 CFR Part 63, Subpart FFFF, the permit holder shall comply with the requirements of 40 CFR § 63.132(a), (a)(1), (a)(1)(i), and (a)(3) as specified in § 63.2485(a) (Title 30 TAC Chapter 113, Subchapter C, § 113.890 incorporated by reference).

### **Additional Monitoring Requirements**

15. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached “CAM Summary” upon issuance of the permit. In addition, the permit holder shall comply with the following:
  - A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).
  - B. The permit holder shall report, consistent with the averaging time identified in the “CAM Summary,” deviations as defined by the deviation limit in the “CAM Summary.” Any monitoring data below a minimum limit or above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).
  - C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the “CAM Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).
  - D. The permit holder shall operate the monitoring, identified in the attached “CAM Summary,” in accordance with the provisions of 40 CFR § 64.7.

- E. The permit holder shall comply with either of the following requirements for any capture system associated with the VOC control device subject to CAM. If the results of the following inspections indicate that the capture system is not working properly, the permit holder shall promptly take necessary corrective actions:
    - (i) Once a year the permit holder shall inspect the capture system in compliance of CAM for leaks in accordance with 40 CFR Part 60, Appendix A, Test Method 21. Leaks shall be indicated by an instrument reading greater than or equal to 500 ppm above background or as defined by the underlying applicable requirement; or
    - (ii) Once a month, the permit holder shall conduct a visual, audible, and/or olfactory inspection of the capture system in compliance of CAM to detect leaking components.
  - F. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.
16. The permit holder shall comply with the periodic monitoring requirements as specified in the attached “Periodic Monitoring Summary” upon issuance of the permit. Except for, as applicable, monitoring malfunctions, associated repairs, and required quality assurance or control activities (including, as applicable, calibration checks and required zero and span adjustments), the permit holder shall conduct all monitoring in continuous operation (or shall collect data at all required intervals) at all times that the pollutant-specific emissions unit is operating. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the “Periodic Monitoring Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances to avoid reporting deviations. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

### **New Source Review Authorization Requirements**

17. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
- A. Are incorporated by reference into this permit as applicable requirements

- B. Shall be located with this operating permit
  - C. Are not eligible for a permit shield
18. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
19. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit's compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, safety data sheets (SDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests, capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

### **Compliance Requirements**

20. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
21. Use of Emission Credits to comply with applicable requirements:
- A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
    - (i) Title 30 TAC Chapter 115
    - (ii) Title 30 TAC Chapter 117
    - (iii) Offsets for Title 30 TAC Chapter 116
  - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:

- (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)(2)
- (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
- (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)(2)
- (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122

22. Use of Discrete Emission Credits to comply with the applicable requirements:

- A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
  - (i) Title 30 TAC Chapter 115
  - (ii) Title 30 TAC Chapter 117
  - (iii) If applicable, offsets for Title 30 TAC Chapter 116
  - (iv) Temporarily exceed state NSR permit allowables
- B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
  - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
  - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
  - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
  - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122

## **Risk Management Plan**

23. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

## **Protection of Stratospheric Ozone**

24. Permit holders at a site subject to Title VI of the FCAA Amendments shall meet the following requirements for protection of stratospheric ozone.
  - A. Any on site servicing, maintenance, and repair on refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants or non-exempt substitutes shall be conducted in accordance with 40 CFR Part 82, Subpart F. Permit holders shall ensure that repairs on or refrigerant removal from refrigeration and nonmotor vehicle air-conditioning appliances using ozone-depleting refrigerants are performed only by properly certified technicians using certified equipment. Records shall be maintained as required by 40 CFR Part 82, Subpart F.

## **Temporary Fuel Shortages (30 TAC § 112.15)**

25. The permit holder shall comply with the following 30 TAC Chapter 112 requirements:
  - A. Title 30 TAC § 112.15 (relating to Temporary Fuel Shortage Plan Filing Requirements)
  - B. Title 30 TAC § 112.16(a), (a)(1), and (a)(2)(B) - (C) (relating to Temporary Fuel Shortage Plan Operating Requirements)
  - C. Title 30 TAC § 112.17 (relating to Temporary Fuel Shortage Plan Notification Procedures)
  - D. Title 30 TAC § 112.18 (relating to Temporary Fuel Shortage Plan Reporting Requirements)

## **Permit Location**

26. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

### **Permit Shield (30 TAC § 122.148)**

27. A permit shield is granted for the emission units, groups, or processes specified in the attached “Permit Shield.” Compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements listed in the attachment “Permit Shield.” Permit shield provisions shall not be modified by the executive director until notification is provided to the permit holder. No later than 90 days after notification of a change in a determination made by the executive director, the permit holder shall apply for the appropriate permit revision to reflect the new determination. Provisional terms are not eligible for this permit shield. Any term or condition, under a permit shield, shall not be protected by the permit shield if it is replaced by a provisional term or condition or the basis of the term and condition changes.

## **Attachments**

**Applicable Requirements Summary**

**Additional Monitoring Requirements**

**Permit Shield**

**New Source Review Authorization References**

### **Applicable Requirements Summary**

<b>Unit Summary .....</b>	<b>19</b>
---------------------------	-----------

<b>Applicable Requirements Summary .....</b>	<b>35</b>
--	-----------

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
900-10.10	STORAGE TANKS/VESSELS	N/A	R5112-01	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
900-10.10	STORAGE TANKS/VESSELS	N/A	634F-10.10	40 CFR Part 63, Subpart FFFF	No changing attributes.
900-10.40	STORAGE TANKS/VESSELS	N/A	R5112-01	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
900-10.40	STORAGE TANKS/VESSELS	N/A	63G-01	40 CFR Part 63, Subpart G	No changing attributes.
900-10.50	STORAGE TANKS/VESSELS	N/A	R5112-01	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
900-10.50	STORAGE TANKS/VESSELS	N/A	63G-01	40 CFR Part 63, Subpart G	No changing attributes.
900-10.60	STORAGE TANKS/VESSELS	N/A	R5112-01	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
900-10.60	STORAGE TANKS/VESSELS	N/A	63G-01	40 CFR Part 63, Subpart G	No changing attributes.
900-10.70	STORAGE TANKS/VESSELS	N/A	R5112-01	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
900-10.70	STORAGE TANKS/VESSELS	N/A	R5112-02	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
900-10.70	STORAGE TANKS/VESSELS	N/A	60KB-01	40 CFR Part 60, Subpart Kb	Storage Vessel Description = Emission controls not required

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					(fixed roof), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
900-10.70	STORAGE TANKS/VESSELS	N/A	60KB-02	40 CFR Part 60, Subpart Kb	Storage Vessel Description = CVS and control device other than a flare (fixed roof), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
900-10.71	STORAGE TANKS/VESSELS	N/A	R5112-01	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
900-10.71	STORAGE TANKS/VESSELS	N/A	R5112-02	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
900-10.71	STORAGE TANKS/VESSELS	N/A	63G-01	40 CFR Part 63, Subpart G	No changing attributes.
900-10.80	STORAGE TANKS/VESSELS	N/A	R5112-01	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
900-10.80	STORAGE TANKS/VESSELS	N/A	R5112-02	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
900-10.80	STORAGE TANKS/VESSELS	N/A	60KB-01	40 CFR Part 60, Subpart Kb	Storage Vessel Description = Emission controls not required (fixed roof), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
900-10.80	STORAGE TANKS/VESSELS	N/A	60KB-02	40 CFR Part 60, Subpart Kb	Storage Vessel Description = CVS and control device other than a flare (fixed roof), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
900-D78.01	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-01	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Vapor recovery system, as defined in 30 TAC § 115.10, other than an afterburner, blast furnace combustion device, boiler, catalytic or direct flame incinerator, carbon adsorption system, chiller, flare or vapor combustor.
900-D78.01	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	R5121-02	30 TAC Chapter 115, Vent Gas Controls	Control Device Type = Smokeless flare
900-D78.01	EMISSION POINTS/STATIONARY VENTS/PROCESS	N/A	634F-D78.01-01	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS				<p>source and 1.9 for an existing source) and a non-flare CD is being used to meet 98% reduction per § 63.2455(a) - Table 1.1.a.i., Designated Grp1 = The emission stream is designated as Group 1., Small Device = A small control device (defined in § 63.2550) is not being used., 1257A1 = No design evaluation as specified in § 63.1257(a)(1) is being conducted., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., CEMS = A CEMS is not used., SS Device Type = Boiler or process heater with a design heat input capacity equal to or greater than 44 megawatts (MW) or in which all vent streams are introduced with the primary fuel or are used as the primary fuel., Meets 63.988(b)(2) = The control device meets criteria in § 63.985(b)(2)., Designated Hal = The emission stream is not designated as halogenated.,</p>

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					Determined Hal = The emission stream is determined to be non-halogenated., Hal Device Type = No halogen scrubber or other halogen reduction device is used., Prior Eval = The data from a prior evaluation or assessment is used., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., Bypass Line = The closed vent system contains no bypass line.
900-D78.01	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	634F-D78.01-02	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a flare is being used for control., Designated Grp1 = The emission stream is designated as Group 1., Designated Hal = The emission stream is not designated as halogenated., Determined Hal = The emission stream is determined to be non-halogenated., Prior Eval = The data from a prior evaluation or assessment is used., Negative Pressure = The closed vent system is operated and

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					maintained at or above atmospheric pressure., Bypass Line = The closed vent system contains no bypass line.
900-D78.01	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	N/A	63G-02	40 CFR Part 63, Subpart G	No changing attributes.
900-FLARE	FLARES	N/A	R1111-01	30 TAC Chapter 111, Visible Emissions	No changing attributes.
900-FLARE	FLARES	N/A	60A-01	40 CFR Part 60, Subpart A	No changing attributes.
900-FLARE	FLARES	N/A	63A-01	40 CFR Part 63, Subpart A	No changing attributes.
900-HAC	LOADING/UNLOADIN G OPERATIONS	N/A	R5212-01	30 TAC Chapter 115, Loading and Unloading of VOC	No changing attributes.
900-HFUG	FUGITIVE EMISSION UNITS	N/A	R5352-ALL	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	No changing attributes.
900-HFUG	FUGITIVE EMISSION UNITS	N/A	63H-ALL	40 CFR Part 63, Subpart H	No changing attributes.
900-MEAC	LOADING/UNLOADIN G OPERATIONS	N/A	R5212-01	30 TAC Chapter 115, Loading and Unloading of VOC	Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
900-MEAC	LOADING/UNLOADING OPERATIONS	N/A	R5212-02	30 TAC Chapter 115, Loading and Unloading of VOC	Chapter 115 Control Device Type = Vapor control system with a flare.
900-MEAC	LOADING/UNLOADING OPERATIONS	N/A	63G-01	40 CFR Part 63, Subpart G	Control Device = Boiler or process heater., Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b)., Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b)., Performance Test Exemption = The design heat input capacity of the boiler or process heater is greater than or equal to 44 MW., Shared Control Device = The control device is shared between transfer racks and process vents., Multiple Arms = Control device is shared between multiple arms loading simultaneously.
900-MEAC	LOADING/UNLOADING OPERATIONS	N/A	63G-02	40 CFR Part 63, Subpart G	Control Device = Flare.
900-MEOH	LOADING/UNLOADING OPERATIONS	N/A	R5212-01	30 TAC Chapter 115, Loading and Unloading of VOC	Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					incinerator, direct flame incinerator, chiller, or carbon adsorption system.
900-MEOH	LOADING/UNLOADING OPERATIONS	N/A	R5212-02	30 TAC Chapter 115, Loading and Unloading of VOC	Chapter 115 Control Device Type = Vapor control system with a flare.
900-MEOH	LOADING/UNLOADING OPERATIONS	N/A	63G-01	40 CFR Part 63, Subpart G	Control Device = Boiler or process heater., Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b)., Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b)., Performance Test Exemption = The design heat input capacity of the boiler or process heater is greater than or equal to 44 MW., Shared Control Device = The control device is shared between transfer racks and process vents., Multiple Arms = Control device is shared between multiple arms loading simultaneously.
900-MEOH	LOADING/UNLOADING OPERATIONS	N/A	63G-02	40 CFR Part 63, Subpart G	Control Device = Flare.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
900-PFUG	FUGITIVE EMISSION UNITS	N/A	63PFUG-FFFF	40 CFR Part 63, Subpart FFFF	No changing attributes.
GRP-MLTKS	STORAGE TANKS/VESSELS	900-10.30, 900- 10.31	R5112-01	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
GRP-MLTKS	STORAGE TANKS/VESSELS	900-10.30, 900- 10.31	63G-01	40 CFR Part 63, Subpart G	No changing attributes.
GRP-POLY1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	901, 902, 903, 904	R5121-01	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
GRP-POLY1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	901, 902, 903, 904	634F-GRPPLY1-01	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new source and 1.9 for an existing source) and a non-flare CD is being used to meet 98% reduction per § 63.2455(a) - Table 1.1.a.i., Designated Grp1 = The emission stream is designated as Group 1., Small Device = A small control device (defined in § 63.2550) is not being used., 1257A1 = No design evaluation as specified in § 63.1257(a)(1) is being conducted., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					<p>approved by the Administrator or have not been requested., CEMS = A CEMS is not used., SS Device Type = Boiler or process heater with a design heat input capacity equal to or greater than 44 megawatts (MW) or in which all vent streams are introduced with the primary fuel or are used as the primary fuel., Meets 63.988(b)(2) = The control device meets criteria in § 63.985(b)(2)., Designated Hal = The emission stream is not designated as halogenated., Determined Hal = The emission stream is determined to be non-halogenated., Hal Device Type = No halogen scrubber or other halogen reduction device is used., Prior Eval = The data from a prior evaluation or assessment is used., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., Bypass Line = The closed vent system contains no bypass line.</p>
GRP-POLY1	EMISSION POINTS/STATIONARY VENTS/PROCESS	901, 902, 903, 904	634F-GRPPLY1- 02	40 CFR Part 63, Subpart FFFF	Emission Standard = The TRE index is not maintained above the threshold (5.0 for a new

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
	VENTS				source and 1.9 for an existing source) and a flare is being used for control., Designated Grp1 = The emission stream is designated as Group 1., Designated Hal = The emission stream is not designated as halogenated., Determined Hal = The emission stream is determined to be non-halogenated., Prior Eval = The data from a prior evaluation or assessment is used., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., Bypass Line = The closed vent system contains no bypass line.
GRP-PTKS	STORAGE TANKS/VESSELS	900-10.20, 900-10.21, 900-10.22, 900-10.23, 900-10.24, 900-10.25	R5112-01	30 TAC Chapter 115, Storage of VOCs	Control Device Type = Other vapor destruction unit
GRP-PTKS	STORAGE TANKS/VESSELS	900-10.20, 900-10.21, 900-10.22, 900-10.23, 900-10.24, 900-10.25	R5112-02	30 TAC Chapter 115, Storage of VOCs	Control Device Type = Flare
GRP-PTKS	STORAGE TANKS/VESSELS	900-10.20, 900-10.21, 900-10.22, 900-10.23, 900-	634F-GRPPTKS-01	40 CFR Part 63, Subpart FFFF	Bypass Line = The closed vent system does not contain a bypass line that could divert the vent

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		10.24, 900-10.25			stream away from the control device., Designated HAL = The emission stream is not designated as halogenated., Determined HAL = The emission stream is determined not to be halogenated., Emission Standard = HAP vapor pressure is greater than or equal to 76.6 and a non-flare CD is being used to meet 95% reduction per § 63.2470(a)-Table 4.1.a.i., SS Device Type = Boiler or process heater with a design heat input capacity equal to or greater than 44 megawatts (MW) or in which all vent streams are introduced with the primary fuel or are used as the primary fuel., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., CEMS = A continuous parameter monitoring system is used., Meets 63.998(b)(2) = The

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					control device meets criteria in § 63.985(b)(2)., HAL Device Type = No halogen scrubber or other halogen reduction device is used., Prior Test = The data from a prior performance test is used.
GRP-PTKS	STORAGE TANKS/VESSELS	900-10.20, 900-10.21, 900-10.22, 900-10.23, 900-10.24, 900-10.25	634F-GRPPTKS-02	40 CFR Part 63, Subpart FFFF	Emission Standard = HAP vapor pressure is greater than or equal to 76.6 and a flare is being used for control per § 63.2470(a)-Table 4.1.a.ii., Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure., Designated HAL = The emission stream is not designated as halogenated., Prior Eval = The data from a prior evaluation or assessment is used., Determined HAL = The emission stream is determined not to be halogenated., Bypass Line = The closed vent system does not contain a bypass line that could divert the vent stream away from the control device.
GRP-PVOH1	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	945, 946	R5121-01	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
GRP-PVOH2	EMISSION POINTS/STATIONARY VENTS/PROCESS VENTS	947, 948, 951, 955, 956, 957	R5121-01	30 TAC Chapter 115, Vent Gas Controls	No changing attributes.
PRO-AAR	CHEMICAL MANUFACTURING PROCESS	N/A	63F-01	40 CFR Part 63, Subpart F	No changing attributes.
REGVLOAD	LOADING/UNLOADIN G OPERATIONS	N/A	R5211-01	30 TAC Chapter 115, Loading and Unloading of VOC	True Vapor Pressure = True vapor pressure less than 0.5 psia., Transfer Type = Only loading.
REGVLOAD	LOADING/UNLOADIN G OPERATIONS	N/A	R5211-02	30 TAC Chapter 115, Loading and Unloading of VOC	True Vapor Pressure = True vapor pressure less than 0.5 psia., Transfer Type = Only unloading.
REGVLOAD	LOADING/UNLOADIN G OPERATIONS	N/A	R5211-03	30 TAC Chapter 115, Loading and Unloading of VOC	True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia., Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized., Chapter 115 Control Device Type = No control device., Transfer Type = Only unloading., Control Options = Vapor balance system., Vapor Tight = All liquid and vapor lines are equipped with fittings which

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					make vapor-tight connections that close automatically when disconnected.
REGVLOAD	LOADING/UNLOADING OPERATIONS	N/A	634F-REGVLD-01	40 CFR Part 63, Subpart FFFF	Emission Standard = A non-flare CD is being used to meet 98% reduction per § 63.2475(a) - Table 5.1.a., Small Device = A small control device (defined in § 63.2550) is not being used., Alt 63SS Mon Parameters = Alternate monitoring parameters or requirements have not been approved by the Administrator or have not been requested., CEMS = Continuous parameter monitoring is used., SS Device Type = Boiler., Meets 63.988(b)(2) = The control device meets criteria in § 63.985(b)(2)., Primary Fuel = All vent streams are introduced with the primary fuel or are used as primary fuel., 44 Primary = The boiler or process heater is either 44 megawatts or greater or the vent stream is introduced as or with primary fuel., Hal Device Type = No halogen scrubber or other halogen reduction device is used

### Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
REGVLOAD	LOADING/UNLOADING OPERATIONS	N/A	634F-REGVLD-02	40 CFR Part 63, Subpart FFFF	Emission Standard = A flare is being used per § 63.2475(a) - Table 5.1.b.

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
900-10.10	EU	R5112-01	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
900-10.10	EU	634F-10.10	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table 4.1.b.i § 63.1062(a) § 63.1062(a)(1) § 63.1063(a)(1)(i) § 63.1063(a)(1)(i)(D) § 63.1063(a)(2)(i) § 63.1063(a)(2)(ii) § 63.1063(a)(2)(iii) § 63.1063(a)(2)(iv) § 63.1063(a)(2)(ix) § 63.1063(a)(2)(v) § 63.1063(a)(2)(vi) § 63.1063(a)(2)(viii) § 63.1063(a)(2)(viii)(B) § 63.1063(b)(1) § 63.1063(b)(2) § 63.1063(b)(3)	For each Group 1 storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you must comply with the requirements of Subpart WW of this part, except as specified in § 63.2470.	§ 63.1063(c)(1) [G]§ 63.1063(c)(1)(i) [G]§ 63.1063(d)(1) § 63.1063(d)(2)	§ 63.1063(e)(2) § 63.1065 § 63.1065(a) [G]§ 63.1065(b)(1) § 63.1065(c) § 63.1065(d)	[G]§ 63.1066(a) § 63.1066(b)(1) § 63.1066(b)(2) § 63.1066(b)(4) § 63.2450(q)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.1063(b)(4) § 63.1063(e)(1) § 63.1063(e)(2) § 63.2470(a)				
900-10.40	EU	R5112-01	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
900-10.40	EU	63G-01	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)				§ 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
900-10.50	EU	R5112-01	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
900-10.50	EU	63G-01	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)				§ 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
900-10.60	EU	R5112-01	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)
900-10.60	EU	63G-01	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(iii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(3)(i) § 63.120(a)(3)(ii) § 63.120(a)(3)(iii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)				§ 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
900-10.70	EU	R5112-01	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
900-10.70	EU	R5112-02	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
900-10.70	EU	60KB-01	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
900-10.70	EU	60KB-02	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(3)	Storage vessels specified in §60.112b(a) and equipped with a closed vent	[G]§ 60.113b(c)(1) § 60.113b(c)(2) § 60.116b(a) § 60.116b(b) § 60.116b(e)	§ 60.115b [G]§ 60.115b(c) § 60.116b(a) § 60.116b(b)	[G]§ 60.113b(c)(1) § 60.115b

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						system/control device are to meet the specifications of §60.112b(a)(3)(i)-(ii). § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b) ** See Periodic Monitoring Summary			
900-10.71	EU	R5112-01	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
900-10.71	EU	R5112-02	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
900-10.71	EU	63G-01	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.120(a)(7)				
900-10.80	EU	R5112-01	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
900-10.80	EU	R5112-02	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
900-10.80	EU	60KB-01	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
900-10.80	EU	60KB-02	VOC	40 CFR Part 60, Subpart Kb	[G]§ 60.112b(a)(3)	Storage vessels specified in §60.112b(a) and equipped with a closed vent system/control device are to meet the specifications of	[G]§ 60.113b(c)(1) § 60.113b(c)(2) § 60.116b(a) § 60.116b(b) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3) [G]§ 60.485(b)	§ 60.115b [G]§ 60.115b(c) § 60.116b(a) § 60.116b(b)	[G]§ 60.113b(c)(1) § 60.115b

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§60.112b(a)(3)(i)-(ii).	** See Periodic Monitoring Summary		
900-D78.01	EP	R5121-01	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(B)	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(C) § 115.126(2) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(C) § 115.126(2)	None
900-D78.01	EP	R5121-02	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.121(a)(2) § 115.122(a)(2) § 115.122(a)(2)(A) § 60.18	No person may allow a vent gas stream to be emitted from the processes specified in §115.121(a)(2)(A)-(E), unless the vent gas stream is controlled properly in accordance with §115.122(a)(2).	[G]§ 115.125 § 115.126(1) § 115.126(1)(B) § 115.126(2) § 115.126(7) ** See CAM Summary	§ 115.126 § 115.126(1) § 115.126(1)(B) § 115.126(2)	None
900-D78.01	EP	634F-D78.01-01	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.i § 63.2450(b) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1)	For each Group 1 continuous process vent, the owner or operator must reduce emissions of total organic HAP by >98 percent by weight by venting emissions through a closed-vent system to any combination of control devices (except flare).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3)	§ 63.2450(k)(6) § 63.2525(g) § 63.2525(h) § 63.983(b) [G]§ 63.983(d)(2) § 63.996(c)(2)(ii) § 63.998(a)(2)(ii)(B)(5) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) [G]§ 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1)	§ 63.2450(q) § 63.996(b)(2) § 63.996(c)(6) § 63.997(b)(1) § 63.997(c)(3) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) [G]§ 63.999(c)(2) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.988(a)(2) § 63.988(a)(3) § 63.988(b)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) § 63.997(b)(1) § 63.997(c)(3)		§ 63.983(d)(1) § 63.983(d)(1)(ii) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(b) § 63.997(b)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii)	§ 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	
900-D78.01	EP	634F-D78.01-02	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.ii § 63.11(b) § 63.2450(b) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.987(a) § 63.997(b)(1) § 63.997(c)(3)	For each Group 1 continuous process vent, the owner or operator must reduce emissions of total organic HAP by venting emissions through a closed vent system to a flare.	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.987(c) § 63.997(b) § 63.997(b)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i) § 63.997(c)(3)(ii)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(c) § 63.998(a)(1)(ii) § 63.998(a)(1)(iii)(A) § 63.998(a)(1)(iii)(B) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.997(b)(1) § 63.997(c)(3) § 63.998(a)(1)(iii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) § 63.999(b)(5) § 63.999(c)(1) [G]§ 63.999(c)(2) § 63.999(c)(3) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv) [G]§ 63.999(d)(1) [G]§ 63.999(d)(2)
900-D78.01	EP	63G-02	112(B) HAPS	40 CFR Part 63, Subpart G	[G]§ 63.113(a)(1) § 63.11 § 63.113(h) [G]§ 63.115(f)	Reduce emissions of organic HAP using a flare. § 63.113(a)(1)(i)-(ii)	§ 63.114(a) § 63.114(a)(2) [G]§ 63.115(f) [G]§ 63.116(a)	[G]§ 63.117(a)(5) § 63.118(a)(1) § 63.118(a)(2) [G]§ 63.152(a) [G]§ 63.152(f)	§ 63.114(e) [G]§ 63.117(a)(5) § 63.117(f) § 63.118(f)(2) § 63.118(f)(5) [G]§ 63.151(b) § 63.151(e) [G]§ 63.151(e)(1)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
									§ 63.151(e)(2) § 63.151(e)(3) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6)
900-FLARE	EU	R1111-01	OPACITY	30 TAC Chapter 111, Visible Emissions	§ 111.111(a)(4)(A)	Visible emissions from a process gas flare shall not be permitted for more than five minutes in any two-hour period, except for emission event emissions as provided in §101.222(b).	§ 111.111(a)(4)(A)(i) § 111.111(a)(4)(A)(ii)	§ 111.111(a)(4)(A)(ii)	None
900-FLARE	CD	60A-01	OPACITY	40 CFR Part 60, Subpart A	§ 60.18(b) § 60.18(c)(1) § 60.18(c)(2) § 60.18(c)(3)(ii) § 60.18(c)(4)(i) § 60.18(c)(6) § 60.18(e)	Flares shall comply with paragraphs (c)-(f) of § 60.18.	§ 60.18(d) § 60.18(f)(1) § 60.18(f)(2) § 60.18(f)(3) § 60.18(f)(4)	None	None
900-FLARE	CD	63A-01	OPACITY	40 CFR Part 63, Subpart A	§ 63.11(b)(4) § 63.11(b)(1) § 63.11(b)(2) § 63.11(b)(3) § 63.11(b)(5) § 63.11(b)(6)(ii)	Flares shall be designed and operated with no visible emissions, except for periods of a total of 5 minutes or	§ 63.11(b)(4) § 63.11(b)(5) § 63.11(b)(7)(i)	None	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.11(b)(7)(i)	less during any 2 consecutive hrs. Test Method 22 in App. A of part 60 of this chapter shall be used.			
900-HAC	EU	R5212-01	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(1) § 115.212(a)(1)(B) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(i) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	At operations other than gasoline terminals, gasoline bulk plants, and marine terminals, vapors of VOC with a true vapor pressure of 0.5 psia or greater, must be controlled by one of the following methods.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(9)	§ 115.216 § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(6)	Components at a petroleum refinery or synthetic organic chemical, polymer, resin, or methyl-tert-butyl ether manufacturing process, that contact a process fluid that contains less than 10% VOC by weight and components at a natural gas/gasoline processing operation that contact a process fluid that contains less than 1.0% VOC by weight are exempt from the requirements of this division except §115.356(3)(C) of this	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						title.			
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(5)	Reciprocating compressors and positive displacement pumps used in natural gas/gasoline processing operations are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(10)	Instrumentation systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet 40 CFR §63.169 (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(11)	Sampling connection systems, as defined in 40 CFR §63.161 (January 17, 1997), that meet the requirements of 40 CFR §63.166(a) and (b) (June 20, 1996) are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(13)	Components/systems that contact a process fluid containing VOC having a true vapor pressure equal to or less than 0.002 psia at 68 degrees Fahrenheit are exempt from the requirements of this division except §115.356(3)(C) of this title.	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.357(2) § 115.352(9)	Each pressure relief valve equipped with a rupture disk must comply with §115.352(9) and §115.356(3)(C).	None	§ 115.356 § 115.356(3) [G]§ 115.356(3)(C)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.353(a) § 115.353(b) § 115.910	For all affected persons in the Beaumont-Port Arthur, Dallas-Fort Worth, El Paso, and Houston-Galveston areas, as defined in §115.10, any alternate methods of demonstrating and documenting continuous compliance with the applicable control requirements or exemption criteria in this division may be approved by the executive director in accordance with	None	None	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						§115.910 if emission reductions are demonstrated to be substantially equivalent.			
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7) § 115.357(1)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(7)	No process drains shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) § 115.356(5)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery	§ 115.352(1)(A) § 115.352(1)	No pressure relief valves shall be	§ 115.354(1) § 115.354(2)	§ 115.352(7) § 115.356	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				& Petrochemicals	§ 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(1) § 115.357(8) § 115.357(9)	allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(9) § 115.357(12) § 115.357(8) § 115.357(9)	No pressure relief valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(4) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.			
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No open-ended valves or lines shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(1) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						sound.			
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(B) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.357(12) § 115.357(8) § 115.357(9)	No valves shall be allowed to have a VOC leak, for more than 15 days after discovery, which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) [G]§ 115.354(7) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	[G]§ 115.354(7)
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(1) § 115.357(12) § 115.357(8)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(11) § 115.354(3) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A)	No flanges or other connectors shall be allowed to have a VOC leak, for more than 15 days after discovery	§ 115.354(1) § 115.354(10) § 115.354(11) § 115.354(3) § 115.354(5)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8) § 115.357(12) § 115.357(8)	which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(1)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding	§ 115.354(1) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(12) § 115.357(8)	of process fluid based on sight, smell, or sound.			
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(A) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(7) § 115.357(12) § 115.357(8)	No agitators shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 500 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(3) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days	[G]§ 115.355	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(4) § 115.357(8)	after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.		§ 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.352(8)	No compressor seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dropping or exuding	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.357(12) § 115.357(8)	of process fluid based on sight, smell, or sound.			
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(1) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355 § 115.357(1)	§ 115.352(7) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) [G]§ 115.356(3)(C) § 115.356(5)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(B) § 115.352(1) § 115.352(10) § 115.352(2) § 115.352(2)(A) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(5) § 115.352(7) § 115.357(12) § 115.357(8)	No pump seals shall be allowed to have a VOC leak, for more than 15 days after discovery which exceeds a screening concentration greater than 10,000 parts per million by volume above background as methane, or the dropping or exuding of process fluid based on sight, smell, or sound.	§ 115.354(1) § 115.354(10) § 115.354(2) § 115.354(5) § 115.354(6) § 115.354(9) [G]§ 115.355	§ 115.352(7) § 115.354(10) § 115.356 [G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) § 115.356(5)	None
900-HFUG	EU	R5352-ALL	VOC	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	§ 115.352(1)(C) § 115.352(1) § 115.352(10) § 115.352(2)	No component shall be allowed to have a VOC leak, for more than 15 days, after	§ 115.354(1) § 115.354(11) § 115.354(13)(A) § 115.354(13)(B)	§ 115.352(7) § 115.354(13)(D) § 115.354(13)(E) § 115.356	[G]§ 115.358(g)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.352(2)(A) § 115.352(2)(B) § 115.352(2)(C) § 115.352(2)(C)(i) § 115.352(2)(C)(ii) § 115.352(2)(C)(iii) § 115.352(3) § 115.352(4) § 115.352(5) § 115.352(6) § 115.352(7) § 115.352(8) § 115.357(8) § 115.358(c)(1) [G]§ 115.358(h)	discovery. If the owner or operator elects to use the alternative work practice in §115.358 of this title, any leak detected as defined in §115.358 of this title, including any leak detected using the alternative work practice on a component that is subject to the requirements of this division but not specifically selected for alternative work practice monitoring.	§ 115.354(13)(C) § 115.354(13)(D) § 115.354(13)(E) § 115.354(13)(F) § 115.354(4) § 115.354(5) § 115.354(9) [G]§ 115.355 § 115.358(c)(2) § 115.358(d) [G]§ 115.358(e) § 115.358(f)	[G]§ 115.356(1) [G]§ 115.356(2) § 115.356(3) § 115.356(3)(A) § 115.356(3)(B) [G]§ 115.356(3)(C) [G]§ 115.356(4) § 115.356(5)	
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.162(e) § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h)	Equipment that is in organic HAP service less than 300 hours per year is excluded from the requirements of §§63.163 - 63.174 and §63.178 if it is identified as required in §63.181(j).	[G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i) § 63.181(j)	[G]§ 63.182(a) [G]§ 63.182(b)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.164 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Compressors. §63.164(a)-(i)	[G]§ 63.164 [G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(f)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B)	40 CFR Part 63,	[G]§ 63.165	Standards: Pressure	[G]§ 63.165	§ 63.181(a)	[G]§ 63.182(a)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart H	§ 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	relief device in gas/vapor service. §63.165(a)-(d)	[G]§ 63.180(b) [G]§ 63.180(c) [G]§ 63.180(d)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(f)	[G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.166 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Sampling connection systems. §63.166(a)-(c)	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pumps in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Valves in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in heavy liquid service. §63.169(a)-(d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators in heavy liquid service. §63.169(a)-	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	(d)		[G]§ 63.181(d) [G]§ 63.181(i)	[G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Instrumentation systems. §63.169(a)- (d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.169 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Pressure relief devices in liquid service. §63.169(a)- (d)	[G]§ 63.169 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.170 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Surge control vessels and bottom receivers.	[G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.172(a) [G]§ 63.172(h) § 63.172(i) § 63.172(m)	Owners/operators of closed-vent systems and control devices used to comply with provisions of this subpart shall comply with the provisions of this section, except as provided in §63.162(b).	[G]§ 63.172(f)(1) [G]§ 63.172(f)(2) § 63.172(g) [G]§ 63.172(h) [G]§ 63.172(l) [G]§ 63.180(b) [G]§ 63.180(d)	[G]§ 63.172(l) § 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) [G]§ 63.181(g)(2) [G]§ 63.181(g)(3)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B)	40 CFR Part 63,	§ 63.172(b)	Vapor recovery	§ 63.172(e)	§ 63.181(a)	[G]§ 63.182(a)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
			HAPS	Subpart H	§ 63.172(e) [G]§ 63.172(h) § 63.172(m)	systems shall be designed and operated to recover the organic HAP emissions or VOC emissions vented to them with an efficiency of 95 percent or greater.	[G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d)	[G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2)	[G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.172(c) § 63.172(e) [G]§ 63.172(h) § 63.172(m)	Enclosed combustion devices shall be designed and operated to reduce the organic HAP or VOC emissions vented to them with requirements as specified in this section.	§ 63.172(e) [G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	§ 63.172(d) § 63.11(b) § 63.172(e) [G]§ 63.172(h) § 63.172(m)	Flares used to comply with this subpart shall comply with the requirements of § 63.11(b) of 40 CFR 63, Subpart A.	§ 63.172(e) [G]§ 63.172(h) [G]§ 63.180(b) [G]§ 63.180(d) [G]§ 63.180(e)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(g) § 63.181(g)(1)(i) § 63.181(g)(1)(ii) § 63.181(g)(1)(iii) § 63.181(g)(1)(iv) [G]§ 63.181(g)(2)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.173 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Agitators gas/vapor service and in light liquid service. §63.173(a)-(j).	[G]§ 63.173 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.174 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171	Standards: Connectors in gas/vapor service and in light liquid service. §63.174(a)-(j)	[G]§ 63.174 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.163 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.176	Standards: Pumps in light liquid service. §63.163(a)-(j)	[G]§ 63.163 [G]§ 63.176 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(3) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) § 63.181(h)(8)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.167 § 63.162(a) § 63.162(c) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Open- ended valves or lines. §63.167(a)-(e).	[G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4) [G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7) [G]§ 63.181(i)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)
900-HFUG	EU	63H-ALL	112(B) HAPS	40 CFR Part 63, Subpart H	[G]§ 63.168 § 63.162(a) § 63.162(c) [G]§ 63.162(f) [G]§ 63.162(g) § 63.162(h) [G]§ 63.171 [G]§ 63.175	Standards: Valves in gas/vapor service and in light liquid service. §63.168(a)-(j)	[G]§ 63.168 [G]§ 63.175 [G]§ 63.180(b) [G]§ 63.180(d)	§ 63.181(a) [G]§ 63.181(b) § 63.181(c) [G]§ 63.181(d) § 63.181(h) [G]§ 63.181(h)(1) [G]§ 63.181(h)(2) § 63.181(h)(4)	[G]§ 63.182(a) [G]§ 63.182(b) § 63.182(c) [G]§ 63.182(c)(1) § 63.182(c)(4) [G]§ 63.182(d)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
								[G]§ 63.181(h)(5) § 63.181(h)(6) § 63.181(h)(7)	
900-MEAC	EU	R5212-01	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(1) § 115.212(a)(1)(A) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(i) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	At operations other than gasoline terminals, gasoline bulk plants, and marine terminals, vapors of VOC with a true vapor pressure of 0.5 psia or greater, must be controlled by one of the following methods.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(9) ** See Periodic Monitoring Summary	§ 115.216 § 115.216(1) § 115.216(1)(C) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	None
900-MEAC	EU	R5212-02	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(1) § 115.212(a)(1)(A) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(i) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.214(a)(1)(B) § 115.214(a)(1)(C) § 60.18	At operations other than gasoline terminals, gasoline bulk plants, and marine terminals, vapors of VOC with a true vapor pressure of 0.5 psia or greater, must be controlled by one of the following methods.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) [G]§ 115.215(3) § 115.215(4) § 115.215(9) § 115.216(1) § 115.216(1)(B)	§ 115.216 § 115.216(1) § 115.216(1)(B) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	None
900-MEAC	EU	63G-01	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.126(a) § 63.126(a)(1) § 63.126(a)(2) § 63.126(a)(3) § 63.126(b)(1) [G]§ 63.126(d)(3) § 63.126(f)	For Group 1 transfer racks shall operate a vapor collection system and control device for organic HAPs.	[G]§ 63.126(d)(3) [G]§ 63.128(f) § 63.148(b)(1)(ii) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(1) § 63.148(g)(2)	§ 63.129(a)(1) § 63.129(a)(4) § 63.129(a)(4)(ii) § 63.129(a)(4)(iv) § 63.130(e) § 63.130(f) § 63.130(f)(1)	§ 63.129(a)(2) § 63.129(a)(3) § 63.129(a)(4) § 63.129(a)(4)(ii) § 63.129(a)(4)(iv) § 63.130(d)(1) § 63.130(d)(2)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.126(g) § 63.126(h) [G]§ 63.148(d) § 63.148(e)		§ 63.148(h) § 63.148(h)(2) § 63.152(g)(1)(i) [G]§ 63.152(g)(1)(ii) § 63.152(g)(1)(iii) § 63.152(g)(1)(iv) [G]§ 63.152(g)(1)(v)	§ 63.130(f)(2) § 63.130(f)(3) § 63.130(f)(3)(ii) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f) § 63.152(g)(1) § 63.152(g)(1)(i) [G]§ 63.152(g)(1)(ii) § 63.152(g)(1)(iii) § 63.152(g)(1)(iv) [G]§ 63.152(g)(1)(v) [G]§ 63.152(g)(1)(vi) § 63.152(g)(2) § 63.152(g)(2)(i) § 63.152(g)(2)(ii) § 63.152(g)(2)(iii)	§ 63.148(j) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6) § 63.152(g)(1) § 63.152(g)(2)(i) § 63.152(g)(2)(ii)
900-MEAC	EU	63G-02	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.126(a) § 63.11 § 63.126(a)(1) § 63.126(a)(2) § 63.126(a)(3) [G]§ 63.126(b)(2) [G]§ 63.126(d)(3) § 63.126(f) § 63.126(g) § 63.126(h) [G]§ 63.148(d) § 63.148(e)	For Group 1 transfer racks shall operate a vapor collection system and control device for organic HAPs.	[G]§ 63.126(d)(3) § 63.127(a) § 63.127(a)(2) § 63.127(e) [G]§ 63.128(b) [G]§ 63.128(f) § 63.148(b)(1)(ii) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(1) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2) § 63.152(g)(1)(i) [G]§ 63.152(g)(1)(ii) § 63.152(g)(1)(iii)	§ 63.129(a)(1) [G]§ 63.129(a)(5) § 63.130(a)(1) § 63.130(a)(2)(i) § 63.130(c) § 63.130(e) § 63.130(f) § 63.130(f)(1) § 63.130(f)(2) § 63.130(f)(3) § 63.130(f)(3)(ii) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4)	§ 63.129(a)(2) § 63.129(a)(3) [G]§ 63.129(a)(5) § 63.130(d)(1) § 63.130(d)(2) § 63.130(d)(5) § 63.148(j) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 63.152(g)(1)(iv) [G]§ 63.152(g)(1)(v)	§ 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f) § 63.152(g)(1) § 63.152(g)(1)(i) [G]§ 63.152(g)(1)(ii) § 63.152(g)(1)(iii) § 63.152(g)(1)(iv) [G]§ 63.152(g)(1)(v) [G]§ 63.152(g)(1)(vi) § 63.152(g)(2) § 63.152(g)(2)(i) § 63.152(g)(2)(ii) § 63.152(g)(2)(iii)	§ 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6) § 63.152(g)(1) § 63.152(g)(2)(i) § 63.152(g)(2)(ii)
900-MEOH	EU	R5212-01	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(1) § 115.212(a)(1)(A) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(i) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	At operations other than gasoline terminals, gasoline bulk plants, and marine terminals, vapors of VOC with a true vapor pressure of 0.5 psia or greater, must be controlled by one of the following methods.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(9) ** See Periodic Monitoring Summary	§ 115.216 § 115.216(1) § 115.216(1)(C) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	None
900-MEOH	EU	R5212-02	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(1) § 115.212(a)(1)(A) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(i) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.214(a)(1)(B)	At operations other than gasoline terminals, gasoline bulk plants, and marine terminals, vapors of VOC with a true vapor pressure of 0.5 psia or greater, must be controlled by one of the following	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) [G]§ 115.215(3)	§ 115.216 § 115.216(1) § 115.216(1)(B) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 115.214(a)(1)(C) § 60.18	methods.	§ 115.215(4) § 115.215(9) § 115.216(1) § 115.216(1)(B)		
900-MEOH	EU	63G-01	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.126(a) § 63.126(a)(1) § 63.126(a)(2) § 63.126(a)(3) § 63.126(b)(1) [G]§ 63.126(d)(3) § 63.126(f) § 63.126(g) § 63.126(h) [G]§ 63.148(d) § 63.148(e)	For Group 1 transfer racks shall operate a vapor collection system and control device for organic HAPs.	[G]§ 63.126(d)(3) [G]§ 63.128(f) § 63.148(b)(1)(ii) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(1) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2) § 63.152(g)(1)(i) [G]§ 63.152(g)(1)(ii) § 63.152(g)(1)(iii) § 63.152(g)(1)(iv) [G]§ 63.152(g)(1)(v)	§ 63.129(a)(1) § 63.129(a)(4) § 63.129(a)(4)(ii) § 63.129(a)(4)(iv) § 63.130(e) § 63.130(f) § 63.130(f)(1) § 63.130(f)(2) § 63.130(f)(3) § 63.130(f)(3)(ii) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f) § 63.152(g)(1) § 63.152(g)(1)(i) [G]§ 63.152(g)(1)(ii) § 63.152(g)(1)(iii) § 63.152(g)(1)(iv) [G]§ 63.152(g)(1)(v) [G]§ 63.152(g)(1)(vi) § 63.152(g)(2) § 63.152(g)(2)(i) § 63.152(g)(2)(ii) § 63.152(g)(2)(iii)	§ 63.129(a)(2) § 63.129(a)(3) § 63.129(a)(4) § 63.129(a)(4)(ii) § 63.129(a)(4)(iv) § 63.130(d)(1) § 63.130(d)(2) § 63.148(j) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6) § 63.152(g)(1) § 63.152(g)(2)(i) § 63.152(g)(2)(ii)
900-MEOH	EU	63G-02	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.126(a) § 63.11 § 63.126(a)(1) § 63.126(a)(2)	For Group 1 transfer racks shall operate a vapor collection system and control	[G]§ 63.126(d)(3) § 63.127(a) § 63.127(a)(2) § 63.127(e)	§ 63.129(a)(1) [G]§ 63.129(a)(5) § 63.130(a)(1) § 63.130(a)(2)(i)	§ 63.129(a)(2) § 63.129(a)(3) [G]§ 63.129(a)(5) § 63.130(d)(1)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.126(a)(3) [G]§ 63.126(b)(2) [G]§ 63.126(d)(3) § 63.126(f) § 63.126(g) § 63.126(h) [G]§ 63.148(d) § 63.148(e)	device for organic HAPs.	[G]§ 63.128(b) [G]§ 63.128(f) § 63.148(b)(1)(ii) [G]§ 63.148(c) § 63.148(g) § 63.148(g)(1) § 63.148(g)(2) § 63.148(h) § 63.148(h)(2) § 63.152(g)(1)(i) [G]§ 63.152(g)(1)(ii) § 63.152(g)(1)(iii) § 63.152(g)(1)(iv) [G]§ 63.152(g)(1)(v)	§ 63.130(c) § 63.130(e) § 63.130(f) § 63.130(f)(1) § 63.130(f)(2) § 63.130(f)(3) § 63.130(f)(3)(ii) § 63.148(g)(2) § 63.148(h)(2) § 63.148(i)(1) § 63.148(i)(2) [G]§ 63.148(i)(4) § 63.148(i)(5) § 63.148(i)(6) [G]§ 63.152(a) [G]§ 63.152(f) § 63.152(g)(1) § 63.152(g)(1)(i) [G]§ 63.152(g)(1)(ii) § 63.152(g)(1)(iii) § 63.152(g)(1)(iv) [G]§ 63.152(g)(1)(v) [G]§ 63.152(g)(1)(vi) § 63.152(g)(2) § 63.152(g)(2)(i) § 63.152(g)(2)(ii) § 63.152(g)(2)(iii)	§ 63.130(d)(2) § 63.130(d)(5) § 63.148(j) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) [G]§ 63.152(b)(2) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(2)(i) [G]§ 63.152(c)(2)(ii) § 63.152(c)(2)(iii) § 63.152(c)(3) § 63.152(c)(3)(i) § 63.152(c)(3)(ii) § 63.152(c)(4)(ii) [G]§ 63.152(c)(6) § 63.152(g)(1) § 63.152(g)(2)(i) § 63.152(g)(2)(ii)
900-PFUG	EU	63PFUG-FFFF	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2480(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart FFFF	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart FFFF
GRP-MLTKS	EU	R5112-01	VOC	30 TAC Chapter	§ 115.112(e)(1)	No person shall place,	§ 115.114(a)(1)	§ 115.118(a)(3)	§ 115.114(a)(1)(B)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Storage of VOCs	§ 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F) [G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.118(a)(3)
GRP-MLTKS	EU	63G-01	112(B) HAPS	40 CFR Part 63, Subpart G	§ 63.119(b) § 63.119(a)(1) [G]§ 63.119(b)(1) § 63.119(b)(2) § 63.119(b)(3)(ii) § 63.119(b)(4) § 63.119(b)(5)(i) § 63.119(b)(5)(ii) § 63.119(b)(5)(iii) § 63.119(b)(5)(iv) § 63.119(b)(5)(v) § 63.119(b)(5)(vi) § 63.119(b)(5)(vii) [G]§ 63.119(b)(5)(viii) § 63.119(b)(6) § 63.120(a)(4) § 63.120(a)(7)	Tanks using a fixed roof and an internal floating roof (defined in §63.111) to comply with §63.119(a)(1) must comply with: §63.119(b)(1)-(6).	§ 63.120(a)(2)(i) § 63.120(a)(2)(ii)	§ 63.120(a)(4) § 63.123(a) § 63.123(c) § 63.123(g) [G]§ 63.152(a)	§ 63.120(a)(5) § 63.120(a)(6) § 63.122(d) § 63.122(d)(1)(ii) § 63.122(d)(1)(iii) § 63.122(d)(2)(ii) § 63.151(a)(7) [G]§ 63.151(b) [G]§ 63.151(j) [G]§ 63.152(a) § 63.152(b) [G]§ 63.152(b)(1) § 63.152(b)(4) § 63.152(c)(1) § 63.152(c)(2) § 63.152(c)(4)(ii)
GRP-POLY1	EP	R5121-01	VOC	30 TAC Chapter	§ 115.127(a)(2)(A)	A vent gas stream	[G]§ 115.125	§ 115.126	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Vent Gas Controls	[G]§ 115.122(a)(4) § 115.127(a)(2)	having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	§ 115.126(2)	§ 115.126(2) § 115.126(4)	
GRP-POLY1	EP	634F-GRPLY1-01	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.i § 63.2450(b) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.988(a)(3) § 63.988(b)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) § 63.997(b)(1) § 63.997(c)(3)	For each Group 1continuous process vent, the owner or operator must reduce emissions of total organic HAP by >98 percent by weight by venting emissions through a closed-vent system to any combination of control devices (except flare).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(b) § 63.997(b)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii)	§ 63.2450(k)(6) § 63.2525(g) § 63.2525(h) § 63.983(b) [G]§ 63.983(d)(2) § 63.996(c)(2)(ii) § 63.998(a)(2)(ii)(B)(5) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.996(b)(2) § 63.996(c)(6) § 63.997(b)(1) § 63.997(c)(3) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) [G]§ 63.999(c)(2) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)
GRP-POLY1	EP	634F-GRPLY1-	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2455(a)-Table 1.1.a.ii	For each Group 1continuous process	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii)	§ 63.2450(f)(2) § 63.2450(f)(2)(i)	§ 63.2450(f)(2)(ii) § 63.2450(q)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
		02			§ 63.11(b) § 63.2450(b) § 63.2455(a) § 63.2455(b) § 63.2455(b)(1) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.987(a) § 63.997(b)(1) § 63.997(c)(3)	vent, the owner or operator must reduce emissions of total organic HAP by venting emissions through a closed vent system to a flare.	§ 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.987(c) § 63.997(b) § 63.997(b)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i) § 63.997(c)(3)(ii)	§ 63.2450(f)(2)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(c) § 63.998(a)(1)(ii) § 63.998(a)(1)(iii)(A) § 63.998(a)(1)(iii)(B) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) [G]§ 63.998(c)(1) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.997(b)(1) § 63.997(c)(3) § 63.998(a)(1)(iii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) § 63.999(b)(5) § 63.999(c)(1) [G]§ 63.999(c)(2) § 63.999(c)(3) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv) [G]§ 63.999(d)(1) [G]§ 63.999(d)(2)
GRP-PTKS	EU	R5112-01	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(3) § 115.112(e)(3)(A) § 115.112(e)(3)(A)(i)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a) § 115.115(a)(6) § 115.116(a)(1) [G]§ 115.117 ** See CAM Summary	§ 115.118(a)(4) § 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	None
GRP-PTKS	EU	R5112-02	VOC	30 TAC Chapter	§ 115.112(e)(1)	No person shall place,	§ 115.115(a)	§ 115.118(a)(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Storage of VOCs	§ 115.112(e)(3) § 115.112(e)(3)(C) § 60.18	store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.	§ 115.115(a)(6) § 115.116(a)(2) [G]§ 115.117 ** See CAM Summary	§ 115.118(a)(4)(F) § 115.118(a)(5) § 115.118(a)(7)	
GRP-PTKS	EU	634F-GRPPTKS-01	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table4.1.b.ii § 63.2450(b) § 63.2450(i)(1) § 63.2450(i)(2) § 63.2470(a) § 63.2470(d) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.990(a)(1) § 63.990(a)(2) § 63.996(c)(1) § 63.996(c)(2)	For each Group 1 storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you may reduce total HAP emissions to < 20 ppmv of TOC or organic HAP and < 20 ppmv of hydrogen halide and halogen HAP by venting emissions through a closed vent system to any combination of control devices (excluding a flare).	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.2470(c)(1) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.990(b)	§ 63.2450(k)(6) § 63.2470(c)(1) § 63.2525(g) § 63.2525(h) § 63.983(b) [G]§ 63.983(d)(2) § 63.990(c) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) § 63.998(a)(2)(ii)(C)(1) § 63.998(a)(2)(ii)(C)(4) § 63.998(a)(2)(ii)(C)(5) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii)	§ 63.2450(q) § 63.2470(d) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) [G]§ 63.999(c)(2) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)		§ 63.990(c) § 63.990(c)(1) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iv) § 63.997(c)(3)(v) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) § 63.997(e)(2)(i)(B) § 63.997(e)(2)(ii) § 63.997(e)(2)(iii) § 63.997(e)(2)(iii)(A) [G]§ 63.997(e)(2)(iii)(B) [G]§ 63.997(e)(2)(iii)(C) [G]§ 63.997(e)(2)(iii)(D) [G]§ 63.997(e)(2)(iii)(E)	§ 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	
GRP-PTKS	EU	634F-GRPPTKS-02	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2470(a)-Table4.1.b.ii § 63.2450(b) § 63.2470(a) § 63.2470(d) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3)	For each Group 1 storage tank for which the maximum true vapor pressure of total HAP at the storage temperature is < 76.6 kilopascals, you may reduce total HAP emissions by > 95 percent by weight by venting emissions through a closed vent system to any	§ 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(5) § 63.2450(k)(5)(i) § 63.2450(k)(5)(ii) § 63.2450(k)(6) § 63.2470(c)(1) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2)	§ 63.2450(k)(5) § 63.2450(k)(5)(iii) § 63.2450(k)(6) § 63.2470(c)(1) § 63.2525(g) § 63.2525(h) § 63.983(b) [G]§ 63.983(d)(2) § 63.990(c) § 63.996(c)(2)(ii) § 63.998(a)(2)(i) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(1)	§ 63.2450(q) § 63.2470(d) § 63.996(b)(2) § 63.996(c)(6) § 63.997(c)(3) § 63.998(a)(2)(ii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(a)(2) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) [G]§ 63.999(c)(2)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.990(a)(1) § 63.990(a)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i) § 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) [G]§ 63.997(c)(1) § 63.997(c)(3) [G]§ 63.997(d)	combination of control devices (excluding a flare).	[G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.990(b) § 63.990(c) § 63.996(b)(1) § 63.996(b)(1)(i) § 63.996(b)(2) § 63.997(a) [G]§ 63.997(c)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iv) § 63.997(c)(3)(v) [G]§ 63.997(d) § 63.997(e) § 63.997(e)(1)(i) [G]§ 63.997(e)(1)(iv) [G]§ 63.997(e)(1)(v) § 63.997(e)(2) § 63.997(e)(2)(i) [G]§ 63.997(e)(2)(i)(A) § 63.997(e)(2)(ii) § 63.997(e)(2)(iv) § 63.997(e)(2)(iv)(A) [G]§ 63.997(e)(2)(iv)(B) § 63.997(e)(2)(iv)(C) § 63.997(e)(2)(iv)(D) § 63.997(e)(2)(iv)(F) § 63.997(e)(2)(iv)(G) [G]§ 63.997(e)(2)(iv)(H)	[G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)
GRP-PVOH1	EP	R5121-01	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).			
GRP-PVOH2	EP	R5121-01	VOC	30 TAC Chapter 115, Vent Gas Controls	§ 115.127(a)(2)(A) [G]§ 115.122(a)(4) § 115.127(a)(2)	A vent gas stream having a combined weight of volatile organic compounds (VOC) < 100 lbs (45.4 kg) in any continuous 24-hour period is exempt from the requirements of § 115.121(a)(1).	[G]§ 115.125 § 115.126(2)	§ 115.126 § 115.126(2) § 115.126(4)	None
PRO-AAR	PRO	63F-01	112(B) HAPS	40 CFR Part 63, Subpart F	§ 63.100(b) [G]§ 63.102(a) [G]§ 63.102(c) § 63.104(a) [G]§ 63.104(d) § 63.104(e) § 63.104(e)(1) [G]§ 63.104(e)(2) § 63.105(d)	Except as provided in paragraphs (b)(4) and (c) of this section, the provisions of subparts F, G, and H apply to chemical manufacturing process units that meet the criteria.	§ 63.103(b)(1) § 63.103(b)(3) § 63.103(b)(4) [G]§ 63.103(b)(5) § 63.103(b)(6) [G]§ 63.104(b)	[G]§ 63.103(c) [G]§ 63.104(e)(2) [G]§ 63.104(f)(1) [G]§ 63.105(b) § 63.105(c) § 63.105(e)	§ 63.103(b)(2) [G]§ 63.103(b)(5) [G]§ 63.103(d) [G]§ 63.104(f)(2)
REGVLOAD	EU	R5211-01	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
REGVLOAD	EU	R5211-02	VOC	30 TAC Chapter	§ 115.217(a)(1)	Vapor pressure (at	§ 115.214(a)(1)(A)	§ 115.216	None

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Loading and Unloading of VOC	§ 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216(2) § 115.216(3)(B)	
REGVLOAD	EU	R5211-03	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.212(a)(3) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(i) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	All land-based VOC transfer to or from transport vessels shall be conducted in the manner specified for leak-free operations.	§ 115.212(a)(3)(B) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii)	§ 115.216 § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(iii)	None
REGVLOAD	EU	634F-REGVLD-01	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2475(a)-Table 5.1.a § 63.2450(b) § 63.2475(a) § 63.982(c) § 63.982(c)(2) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.988(a)(1) § 63.988(a)(2) § 63.988(a)(3) § 63.988(b)(2) § 63.996(c)(1) § 63.996(c)(2) § 63.996(c)(2)(i)	For each Group 1 transfer rack you must reduce emissions of total organic HAP by > 98 percent by weight.	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.2450(g) § 63.2450(g)(1) § 63.2450(g)(2) [G]§ 63.2450(g)(3) § 63.2450(g)(4) § 63.2450(k)(6) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.996(b)(1) § 63.996(b)(1)(i)	§ 63.2450(k)(6) § 63.2525(g) § 63.2525(h) § 63.983(b) [G]§ 63.983(d)(2) § 63.996(c)(2)(ii) § 63.998(a)(2)(ii)(B)(5) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) § 63.998(c)(2)(iii) § 63.998(c)(3)(iii) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(q) § 63.996(b)(2) § 63.996(c)(6) § 63.997(b)(1) § 63.997(c)(3) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) [G]§ 63.999(b)(3) § 63.999(b)(5) § 63.999(c)(1) [G]§ 63.999(c)(2) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv)

## Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					§ 63.996(c)(3) § 63.996(c)(4) § 63.996(c)(5) § 63.996(c)(6) § 63.997(b)(1) § 63.997(c)(3)		§ 63.996(b)(2) § 63.997(b) § 63.997(b)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(iii)		
REGVLOAD	EU	634F-REGVLD-02	112(B) HAPS	40 CFR Part 63, Subpart FFFF	§ 63.2475(a)-Table 5.1.b § 63.11(b) § 63.2450(b) § 63.2475(a) § 63.982(b) § 63.983(a)(1) § 63.983(a)(2) § 63.983(d)(1) § 63.983(d)(1)(i) [G]§ 63.983(d)(2) § 63.983(d)(3) § 63.987(a) § 63.997(b)(1) § 63.997(c)(3)	For each Group 1 transfer rack you must reduce emissions of total organic HAP by venting emissions through a closed-vent system to a flare.	[G]§ 63.115(d)(2)(v) § 63.115(d)(3)(iii) § 63.983(b) [G]§ 63.983(b)(1) [G]§ 63.983(b)(2) [G]§ 63.983(b)(3) [G]§ 63.983(c)(1) § 63.983(c)(2) § 63.983(c)(3) § 63.983(d)(1) § 63.983(d)(1)(ii) § 63.987(c) § 63.997(b) § 63.997(b)(1) § 63.997(c)(2) § 63.997(c)(3) § 63.997(c)(3)(i)	§ 63.2450(f)(2) § 63.2450(f)(2)(i) § 63.2450(f)(2)(ii) § 63.983(b) [G]§ 63.983(d)(2) § 63.987(c) § 63.998(a)(1)(ii) § 63.998(a)(1)(iii)(A) § 63.998(a)(1)(iii)(B) [G]§ 63.998(b)(1) [G]§ 63.998(b)(2) [G]§ 63.998(b)(3) [G]§ 63.998(b)(5) [G]§ 63.998(c)(1) [G]§ 63.998(d)(1) § 63.998(d)(3)(i) § 63.998(d)(3)(ii) § 63.998(d)(5)	§ 63.2450(f)(2)(ii) § 63.2450(q) § 63.997(b)(1) § 63.997(c)(3) § 63.998(a)(1)(iii)(A) [G]§ 63.998(b)(3) [G]§ 63.999(a)(1) § 63.999(b)(5) § 63.999(c)(1) [G]§ 63.999(c)(2) § 63.999(c)(3) § 63.999(c)(6) [G]§ 63.999(c)(6)(i) § 63.999(c)(6)(iv) [G]§ 63.999(d)(1) [G]§ 63.999(d)(2)

**Additional Monitoring Requirements**

**Compliance Assurance Monitoring Summary ..... 76**

**Periodic Monitoring Summary.....80**

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: 900-D78.01	
Control Device ID No.: 800-B15.50	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-01
Pollutant: VOC	Main Standard: § 115.121(a)(2)
<b>Monitoring Information</b>	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Monitor and record the periods of operation of the boiler. All periods when the boiler is operating as a control device that are not recorded shall be considered and reported as a deviation.	
CAM Text: Monitor and record the periods of operation of the steam generating units or process heater. The records must be readily available for inspection.	

## CAM Summary

Unit/Group/Process Information	
ID No.: 900-D78.01	
Control Device ID No.: 900-FLARE	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-02
Pollutant: VOC	Main Standard: § 115.121(a)(2)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Any absence of a flare pilot flame when not routed to the primary control device (boiler) shall be reported as a deviation.	
<p>CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.</p>	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: GRP-PTKS	
Control Device ID No.: 800-B15.50	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-01
Pollutant: VOC	Main Standard: § 115.112(e)(1)
<b>Monitoring Information</b>	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Monitor and record the periods of operation of the boiler. All periods when the boiler is operating as a control device that are not recorded shall be considered and reported as a deviation.	
CAM Text: Monitor and record the periods of operation of the steam generating units or process heater. The records must be readily available for inspection.	

## CAM Summary

<b>Unit/Group/Process Information</b>	
ID No.: GRP-PTKS	
Control Device ID No.: 900-FLARE	Control Device Type: Flare
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-02
Pollutant: VOC	Main Standard: § 115.112(e)(1)
<b>Monitoring Information</b>	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: Any absence of a flare pilot flame when not routed to the primary control device (boiler) shall be reported as a deviation.	
CAM Text: Monitor the presence of a flare pilot flame using a thermocouple or other equivalent device to detect the presence of a flame or using an alarm that uses a thermocouple or other equivalent device to detect the absence of a flame. Maintain records of alarm events and duration of alarm events. Each monitoring device shall be accurate to within manufacturer's recommendations. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications or other written procedures that provide an adequate assurance that the device is calibrated accurately.	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: 900-10.70	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-02
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
<b>Monitoring Information</b>	
Indicator: VOC Concentration	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if there are detectable emissions of 500 ppm or greater above background and/or VOC concentrations are not measured and recorded.	
Periodic Monitoring Text: Measure and record fugitive emissions from the vapor collection system in accordance with part 60, appendix A, method 21.	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: 900-10.70	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-02
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
<b>Monitoring Information</b>	
Indicator: Visual Inspection	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if defects in the closed vent system are detected or if the components are not inspected.	
Periodic Monitoring Text: Visually inspect all components of the vapor collection system for defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	

## Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 900-10.70	
Control Device ID No.: 987-SCRUB	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-02
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: Scrubber inlet liquid flow rate	
Minimum Frequency: Continuously	
Averaging Period: 1 hour	
Deviation Limit: Minimum liquid flow to Acetic Acid Scrubber shall be 60 gallons per hour.	
<p>Periodic Monitoring Text: Monitor and record the minimum flow to the Acetic Acid Scrubber to demonstrate a 99 percent removal efficiency and a minimum 60 gallons per hour flow. Acetic Acid Scrubber shall operate with no less than 99 percent removal efficiency for Acetic Acid on a rolling 1-hour average. The minimum liquid flow to the Acetic Acid Scrubber shall be 60 gallons per hour. The circulation rate shall be monitored and compliance with the minimum liquid flowrate shall be demonstrated by recording the alarm output at least once per hour. It shall be considered a deviation if the removal efficiency of the scrubber is less than 99 percent and/or the flowrate is less than 60 gallons per hour.</p> <p>The flow monitoring device shall be calibrated at least annually and shall be accurate to within 2 percent of span or 5 percent of the design value. Quality assured (or valid) data must be generated when the scrubber is operating except during the performance of a daily zero check. Loss of valid data due to periods of monitor breakdown, out-of-control operation, repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in hours) that the device operated over the previous rolling 12-month period. It shall be considered a deviation if calibrations are not done annually following the accuracy described above, and/or loss of valid data exceeds 5 percent of the time on a 12 month- rolling total period.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: 900-10.80	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-02
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
<b>Monitoring Information</b>	
Indicator: VOC Concentration	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if there are detectable emissions of 500 ppm or greater above background and/or VOC concentrations are not measured and recorded.	
Periodic Monitoring Text: Measure and record fugitive emissions from the vapor collection system in accordance with part 60, appendix A, method 21.	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: 900-10.80	
Control Device ID No.: N/A	Control Device Type: N/A
<b>Applicable Regulatory Requirement</b>	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-02
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
<b>Monitoring Information</b>	
Indicator: Visual Inspection	
Minimum Frequency: Once per year	
Averaging Period: n/a	
Deviation Limit: It shall be considered a deviation if defects in the closed vent system are detected or if the components are not inspected.	
Periodic Monitoring Text: Visually inspect all components of the vapor collection system for defects, such as cracks, holes, gaps, loose connections, or broken or missing covers or other closure devices, that could result in air emissions.	

## Periodic Monitoring Summary

Unit/Group/Process Information	
ID No.: 900-10.80	
Control Device ID No.: 987-SCRUB	Control Device Type: Wet Scrubber
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart Kb	SOP Index No.: 60KB-02
Pollutant: VOC	Main Standard: [G]§ 60.112b(a)(3)
Monitoring Information	
Indicator: Scrubber inlet liquid flow rate	
Minimum Frequency: Continuously	
Averaging Period: 1 hour	
Deviation Limit: Minimum liquid flow to Acetic Acid Scrubber shall be 60 gallons per hour.	
<p>Periodic Monitoring Text: Monitor and record the minimum flow to the Acetic Acid Scrubber to demonstrate a 99 percent removal efficiency and a minimum 60 gallons per hour flow. Acetic Acid Scrubber shall operate with no less than 99 percent removal efficiency for Acetic Acid on a rolling 1-hour average. The minimum liquid flow to the Acetic Acid Scrubber shall be 60 gallons per hour. The circulation rate shall be monitored and compliance with the minimum liquid flowrate shall be demonstrated by recording the alarm output at least once per hour. It shall be considered a deviation if the removal efficiency of the scrubber is less than 99 percent and/or the flowrate is less than 60 gallons per hour.</p> <p>The flow monitoring device shall be calibrated at least annually and shall be accurate to within 2 percent of span or 5 percent of the design value. Quality assured (or valid) data must be generated when the scrubber is operating except during the performance of a daily zero check. Loss of valid data due to periods of monitor breakdown, out-of-control operation, repair, maintenance, or calibration may be exempted provided it does not exceed 5 percent of the time (in hours) that the device operated over the previous rolling 12-month period. It shall be considered a deviation if calibrations are not done annually following the accuracy described above, and/or loss of valid data exceeds 5 percent of the time on a 12 month- rolling total period.</p>	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: 900-MEAC	
Control Device ID No.: 800-B15.50	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5212-01
Pollutant: VOC	Main Standard: § 115.212(a)(1)
<b>Monitoring Information</b>	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Monitor and record the periods of operation of the boiler. All periods when the boiler is operating as a control device that are not recorded shall be considered and reported as a deviation.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

## Periodic Monitoring Summary

<b>Unit/Group/Process Information</b>	
ID No.: 900-MEOH	
Control Device ID No.: 800-B15.50	Control Device Type: Steam Generating Unit (Boiler)/Process Heater (Design heat input is greater than or equal to 44MW)
<b>Applicable Regulatory Requirement</b>	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: R5212-01
Pollutant: VOC	Main Standard: § 115.212(a)(1)
<b>Monitoring Information</b>	
Indicator: Period of Operation	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Monitor and record the periods of operation of the boiler. All periods when the boiler is operating as a control device that are not recorded shall be considered and reported as a deviation.	
Periodic Monitoring Text: Monitor and record the periods of operation of the steam generating units or process heater. All periods that are not recorded shall be considered and reported as a deviation. The records must be readily available for inspection.	

**Permit Shield**

**Permit Shield .....89**

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/ Inclusive Units		
900-10.10	N/A	40 CFR Part 60, Subpart Kb	Storage tank assigned to an MCPU elects to comply only with the requirements for Group 1 storage tanks in 40 CFR Part 63, Subpart FFFF.
900-10.10	N/A	40 CFR Part 63, Subpart G	Unit is not part of a HON CMPU.
900-10.10	N/A	40 CFR Part 63, Subpart OO	The tank is not subject to another subpart within 40 CFR Part 60, 61 or 63 that references this subpart for the control of air emissions.
900-10.40	N/A	40 CFR Part 60, Subpart Kb	40 CFR Part 60, Subpart Kb is superseded by HON 40 CFR Part 63, Subpart G (Group 1 vessel).
900-10.40	N/A	40 CFR Part 63, Subpart OO	The tank is not subject to another subpart within 40 CFR Part 60, 61 or 63 that references this subpart for the control of air emissions.
900-10.50	N/A	40 CFR Part 60, Subpart Kb	40 CFR Part 60, Subpart Kb is superseded by HON 40 CFR Part 63, Subpart G (Group 1 vessel).
900-10.50	N/A	40 CFR Part 63, Subpart OO	The tank is not subject to another subpart within 40 CFR Part 60, 61 or 63 that references this subpart for the control of air emissions.
900-10.60	N/A	40 CFR Part 60, Subpart Kb	40 CFR Part 60, Subpart Kb is superseded by HON 40 CFR Part 63, Subpart G (Group 1 vessel).
900-10.60	N/A	40 CFR Part 63, Subpart OO	The tank is not subject to another subpart within 40 CFR Part 60, 61 or 63 that references this subpart for the control of air

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/ Inclusive Units		
			emissions.
900-10.70	N/A	40 CFR Part 63, Subpart OO	The tank is not subject to another subpart within 40 CFR Part 60, 61 or 63 that references this subpart for the control of air emissions.
900-10.80	N/A	40 CFR Part 63, Subpart G	Unit does not store organic HAPs.
900-10.80	N/A	40 CFR Part 63, Subpart OO	The tank is not subject to another subpart within 40 CFR Part 60, 61 or 63 that references this subpart for the control of air emissions.
900-60.01	N/A	40 CFR Part 60, Subpart Kb	Storage vessel has a capacity greater than or equal to 151 m3 and stores a liquid with maximum true vapor pressure less than 3.5 kPa.
900-60.01	N/A	40 CFR Part 63, Subpart OO	The tank is not subject to another subpart within 40 CFR Part 60, 61 or 63 that references this subpart for the control of air emissions.
900-72.01	N/A	40 CFR Part 63, Subpart Q	Unit does not operate with chromium-based water treatment chemicals on or after 09/08/94.
900-D78.01	N/A	40 CFR Part 60, Subpart NNN	Unit is not part of a SOCFI distillation operation.
900-HAC	N/A	40 CFR Part 63, Subpart G	Operations does not include loading of organic HAPs.
900-PFUG	N/A	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	Fugitives are not part of a petroleum refinery, natural gas/gasoline processing operation or petrochemical process.

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/ Inclusive Units		
900-PFUG	N/A	40 CFR Part 60, Subpart VV	Affected sources are not part of a SOCM I.
900-PFUG	N/A	40 CFR Part 63, Subpart H	Affected sources are not part of a HON C MPU.
900-R52.01	N/A	40 CFR Part 60, Subpart RRR	40 CFR Part 60, Subpart RRR superseded by HON 40 CFR Part 63, Subpart G requirements applicable to 900-D78.01.
900-R52.02	N/A	40 CFR Part 60, Subpart RRR	40 CFR Part 60, Subpart RRR superseded by HON 40 CFR Part 63, Subpart G requirements applicable to 900-D78.01.
900-T21.02	N/A	40 CFR Part 60, Subpart NNN	Unit is not part of a SOCM I distillation operation.
900-T21.02	N/A	40 CFR Part 63, Subpart G	Unit is not part of a HON C MPU.
900-T78.01	N/A	40 CFR Part 60, Subpart NNN	Unit is not part of a SOCM I distillation operation.
900-T78.01	N/A	40 CFR Part 63, Subpart G	Unit is not part of a HON C MPU.
GRP-ATWR	900-T52.01, 900-T52.02, 900-T52.03, 900-T52.04, 900-T52.05	40 CFR Part 60, Subpart NNN	40 CFR Part 60, Subpart NNN is superseded by 40 CFR Part 63, Subpart G requirements applicable to 900-D78.01.
GRP-MLTKS	900-10.30, 900-10.31	40 CFR Part 60, Subpart Kb	40 CFR Part 60, Subpart Kb is superseded by HON 40 CFR Part 63, Subpart G (Group 1 vessel).
GRP-MLTKS	900-10.30, 900-10.31	40 CFR Part 63, Subpart OO	The tanks are not subject to another subpart within 40 CFR Part 60, 61 or 63 that references this subpart for the control of air emissions.
GRP-PKR	900-R2101A, 900-R2101B	40 CFR Part 60, Subpart III	Units are not SOCM I air oxidation reactors.

## Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/ Inclusive Units		
GRP-PKR	900-R2101A, 900-R2101B	40 CFR Part 60, Subpart RRR	Units are not SOCMI reactors.
GRP-POLY1	901, 902, 903, 904	40 CFR Part 63, Subpart G	Units are not part of a HON CMPU.
GRP-PTKS	900-10.20, 900-10.21, 900-10.22, 900-10.23, 900-10.24, 900-10.25	40 CFR Part 60, Subpart Kb	Storage tank assigned to an MCPU elects to comply only with the requirements for Group 1 storage tanks in 40 CFR Part 63, Subpart FFFF.
GRP-PTKS	900-10.20, 900-10.21, 900-10.22, 900-10.23, 900-10.24, 900-10.25	40 CFR Part 63, Subpart G	Units are not part of a HON CMPU.
GRP-PTKS	900-10.20, 900-10.21, 900-10.22, 900-10.23, 900-10.24, 900-10.25	40 CFR Part 63, Subpart OO	The tanks are not subject to another subpart within 40 CFR Part 60, 61 or 63 that references this subpart for the control of air emissions.
GRP-PVOH1	945, 946	40 CFR Part 60, Subpart NNN	Units are not part of a SOCMI distillation operation.
GRP-PVOH1	945, 946	40 CFR Part 63, Subpart G	Units are not part of a HON CMPU.
GRP-PVOH2	947, 948, 951, 955, 956, 957	40 CFR Part 60, Subpart NNN	Units are not part of a SOCMI distillation operation.
GRP-PVOH2	947, 948, 951, 955, 956, 957	40 CFR Part 63, Subpart G	Units are not part of a HON CMPU.
GRP-SAPR	900-R31.01, 900-R32.01	40 CFR Part 60, Subpart III	Units are not SOCMI air oxidation reactors.
GRP-SAPR	900-R31.01, 900-R32.01	40 CFR Part 60, Subpart RRR	Units are not SOCMI reactors.

### Permit Shield

The Executive Director of the TCEQ has determined that the permit holder is not required to comply with the specific regulation(s) identified for each emission unit, group, or process in this table.

Unit/Group/Process		Regulation	Basis of Determination
ID No.	Group/ Inclusive Units		
GRP-VTWR	900-T51.01, 900-T51.02, 900-T51.03	40 CFR Part 60, Subpart NNN	Units are not part of a SOCMI distillation operation.
PRO-PVOH	N/A	40 CFR Part 63, Subpart F	Affected source is not part of a HON CMPU.

**New Source Review Authorization References**

**New Source Review Authorization References ..... 95**

**New Source Review Authorization References by Emission Unit..... 96**

## New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

<b>Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.</b>	
Authorization No.: 19618	Issuance Date: 02/27/2015
<b>Permits By Rule (30 TAC Chapter 106) for the Application Area</b>	
Number: 106.122	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 09/04/2000
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.264	Version No./Date: 09/04/2000
Number: 106.372	Version No./Date: 09/04/2000
Number: 106.373	Version No./Date: 09/04/2000
Number: 106.452	Version No./Date: 09/04/2000
Number: 106.454	Version No./Date: 11/01/2001
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.475	Version No./Date: 03/14/1997
Number: 106.475	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
900-10.10	TK-10.10 VINYL ACETATE REWORK TANK	19618
900-10.20	TK-10.20 PASTE STORAGE TANK	19618, 106.475/03/14/1997
900-10.21	TK-10.21 PASTE STORAGE TANK	19618, 106.475/03/14/1997
900-10.22	TK-10.22 PASTE STORAGE TANK	19618, 106.475/03/14/1997
900-10.23	TK-10.23 PASTE STORAGE TANK	19618, 106.475/03/14/1997
900-10.24	TK-10.24 PASTE STORAGE TANK	19618, 106.262/11/01/2003, 106.475/03/14/1997
900-10.25	TK-10.25 PASTE STORAGE TANK	19618, 106.475/03/14/1997
900-10.30	TK-10.30 MOTHER LIQUOR STORAGE TANK	19618, 106.478/09/04/2000
900-10.31	TK-10.31 MOTHER LIQUOR STORAGE TANK	19618
900-10.40	TK-10.40 FRESH METHANOL TANK	19618, 106.261/11/01/2003, 106.262/11/01/2003
900-10.50	TK-10.50 RECOVERED METHANOL TANK	19618
900-10.60	TK-10.60 SEAL FLUSH METHANOL AND VAM REWORK TANK	19618
900-10.70	TK-10.70 METHYL ACETATE STORAGE TANK	19618, 106.261/11/01/2003, 106.262/11/01/2003
900-10.71	TK-10.71 METHYL ACETATE STORAGE TANK	19618
900-10.80	TK-10.80 ACETIC ACID STORAGE TANK	19618, 106.261/11/01/2003, 106.262/11/01/2003

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
900-60.01	TK-60.01 WASTEWATER STORAGE TANK	19618
900-72.01	PK-72.01 PROCESS COOLING TOWER	19618
900-D78.01	D-78.01 VENT RECOVERY KO DRUM	19618
900-FLARE	FS-78.01 PVOH BACKUP FLARE	19618, 106.262/11/01/2003
900-HAC	ACETIC ACID LOADING/UNLOADING	19618
900-HFUG	HON FUGITIVES	19618, 106.262/11/01/2003, 106.263/11/01/2001
900-MEAC	METHYL ACETATE LOADING/UNLOADING	106.262/09/04/2000
900-MEOH	METHONAL LOADING/UNLOADING	19618
900-PFUG	NON-HON FUGITIVES	19618, 106.262/11/01/2003, 106.263/11/01/2001
900-R2101A	R-21.01A POLYKETTLE REACTOR NO.1	19618
900-R2101B	R-21.01B POLYKETTLE REACTOR NO.2	19618
900-R31.01	R-31.01 SAPONIFICATION REACTOR NO. 1	19618
900-R32.01	R-32.01 SAPONIFICATION REACTOR NO. 2	19618
900-R52.01	R-52.01 ION EXCHANGE REACTOR	19618
900-R52.02	R-52.02 CHLORIDE REMOVAL RACTOR	19618
900-T21.02	T-21.02 PASTE STRIPPER	19618

### New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
900-T51.01	T-51.01 VINYL EXTRACT TOWER	19618
900-T51.02	T-51.02 VINYL RECOVERY TOWER	19618
900-T51.03	T-51.03 VINYL REDISTILLATION TOWER	19618
900-T52.01	T-52.01 METHYL EXTRACT TOWER	19618
900-T52.02	T-52.02 METHANOL TOWER	19618
900-T52.03	T-52.03 ALDEHYDE TOWER	19618
900-T52.04	T-52.04 CRUDE ACID TOWER	19618
900-T52.05	T-52.05 ACID PRODUCT TOWER	19618
900-T78.01	T-78.01 WASTE WATER STRIPPER	19618
901	D-21.01 A/B INITIATOR PREPARATION DRUM STACK	19618
902	D-51.06 INHIBITOR PREPARATION DRUM STACK	19618
903	D-21.04 STOPPER PREPARATION DRUM STACK	19618
904	D-21.07 PHOSPHORIC ACID PREPARATION DRUM STACK	19618
945	DRY GRINDING VENT 1	19618
946	DRY GRINDING VENT 2	19618
947	MILL RECYCLE VENT 1	19618
948	MILL RECYCLE VENT 2	19618
951	GROUND PRODUCT SILO	19618

### **New Source Review Authorization References by Emissions Unit**

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

<b>Unit/Group/Process ID No.</b>	<b>Emission Unit Name/Description</b>	<b>New Source Review Authorization</b>
955	HOUSE VACUUM VENT	19618
956	BULK LOADING SILO 1	19618
957	BULK LOADING SILO 2	19618
PRO-AAR	ACETIC ACID RECOVERY PROCESS	19618
PRO-PVOH	PVOH PROCESS	19618
REGVLOAD	SITE LOADING/UNLOADING	19618, 106.262/11/01/2003, 106.263/11/01/2001

## **Appendix A**

<b>Acronym List .....</b>	<b>101</b>
---------------------------	------------

## Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM .....	actual cubic feet per minute
AMOC .....	alternate means of control
ARP .....	Acid Rain Program
ASTM .....	American Society of Testing and Materials
B/PA .....	Beaumont/Port Arthur (nonattainment area)
CAM .....	Compliance Assurance Monitoring
CD .....	control device
COMS .....	continuous opacity monitoring system
CVS .....	closed-vent system
D/FW .....	Dallas/Fort Worth (nonattainment area)
DR .....	Designated Representative
ELP .....	El Paso (nonattainment area)
EP .....	emission point
EPA .....	U.S. Environmental Protection Agency
EU .....	emission unit
FCAA Amendments .....	Federal Clean Air Act Amendments
FOP .....	federal operating permit
GF .....	grandfathered
gr/100 scf .....	grains per 100 standard cubic feet
HAP .....	hazardous air pollutant
H/G/B .....	Houston/Galveston/Brazoria (nonattainment area)
H <sub>2</sub> S .....	hydrogen sulfide
ID No. ....	identification number
lb/hr .....	pound(s) per hour
MMBtu/hr .....	Million British thermal units per hour
MRRT .....	monitoring, recordkeeping, reporting, and testing
NA .....	nonattainment
N/A .....	not applicable
NADB .....	National Allowance Data Base
NO <sub>x</sub> .....	nitrogen oxides
NSPS .....	New Source Performance Standard (40 CFR Part 60)
NSR .....	New Source Review
ORIS .....	Office of Regulatory Information Systems
Pb .....	lead
PBR .....	Permit By Rule
PM .....	particulate matter
ppmv .....	parts per million by volume
PSD .....	prevention of significant deterioration
RO .....	Responsible Official
SO <sub>2</sub> .....	sulfur dioxide
TCEQ .....	Texas Commission on Environmental Quality
TSP .....	total suspended particulate
TVP .....	true vapor pressure
U.S.C. ....	United States Code
VOC .....	volatile organic compound